



10 mil Multi-Purpose Duct Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Silver, Black, Red, White, OD, Blue, Green, Brown, Tan, Yellow
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- Hanging and seaming poly sheeting
- Color coding
- Sealing and closure tape for poly bags
- Temporary holding and bundling

Features

PE-Coated Cloth Backing

Natural Rubber Based Adhesive

Low VOC Content

Benefits

- Good balance of tensile strength and tearability
- Conformable and moisture resistant
- Excellent adhesion to a variety of surfaces
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	10 mils	0.254 mm	ASTM D-1000
Adhesion to Steel	80 oz/in	8.8 N/cm	PSTC-101
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	25 lb/in	43.8 N/cm	ASTM D-1000
Elongation	24 %		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.