



Backing Carrier: None
Standard Colors: Gray
Base: Non-drying synthetic polymers & oils

Applications

- Sealing electrical conduit openings and joints against water infiltration
- Sealing against water and dirt in electrical pot heads, terminal boxes, electrical bushings, and more
- Sealing around steel conduits where they enter an exposed junction
- Dampening panel noise and vibration in switch gear

Features

Polymer/Oil Blend

Benefits

- Adheres to a variety of surfaces
- Non-Staining
- Paintable
- Excellent resistance to water, alcohols, mild acids and bases
- Excellent aging characteristics - will not dry out over time
- Tested in accordance with UL 723

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Flame Spread Index	5		
Smoke Developed Index	10		
Dielectric Strength	100 volts/mil		ASTM D149-64
Application Temperature	25 to 120 °F	-4 to 49 °C	
Operating Temperature	-30 to 175 °F	-34 to 80 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.