



Premium Butyl Brush-on Primer



Base:

Rubber/Resins

Solvent:

V. M. & P Naptha

Applications

- Surface preparation for masonry, concrete, OSB, rigid insulation, wood, and metal
- Promotes adhesion and anchorage prior to installation of window, door and roof flashing
- Brush or roller priming applications
- Promotes adhesion and anchorage prior to installation of pipe wrap tapes

Features

Rubber Based

Benefits

- Good UV, moisture, and oxidation resistance
- Dries to a smooth, uniform finish to provide a superior bonding surface
- Easy to apply, no over-spray

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Weight (Per Gallon)	7.1 lb/gal	0.86 kg/L	
Total Solids	30		
Flash Point	40 °F	-4 °C	
Installation Temperature	50 to 120 °F	10 to 49 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.