



Double-Coated Cloth Carpet and Mounting Tape



Backing Carrier:	Cloth
Adhesive AS/LS:	Rubber
Release Liner:	Blue LDPE or Blue PP
Standard Colors:	Natural (adhesive color)
Specifications:	Boeing BAC5034-4 Section 5.1.a(1)(a)
Note:	Colors: Natural (adhesive color)
Standard Sizes:	48mm x 23M, 48mm x 33M, 72mm x 23M

Applications

- Carpet hold-down for the convention and entertainment industry
- General mounting and holding
- Hanging, seaming, and splicing poly sheeting

Features

Benefits

Cloth reinforcement

- Good strength and elongation for easy tear, application and removal
- Conformable and moisture resistant

Natural rubber based adhesive

- Clean removal from most surfaces
- High tack and aggressive adhesion for a secure bond

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	40 oz/in	4.38 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		