



Double-Coated Cloth Carpet and Mounting Tape



- Backing Carrier: Cloth
- Adhesive AS/LS: Rubber
- Release Liner: Blue LDPE or Blue PP
- Standard Colors: Natural (adhesive color)
- Specifications: Boeing BAC5034-4 Section 5.1.a(1)(a)
- Note: Colors: Natural (adhesive color)
- Standard Sizes: 48mm x 23M, 48mm x 33M, 72mm x 23M

Applications

- Carpet hold-down for the convention and entertainment industry
- General mounting and holding
- Hanging, seaming, and splicing poly sheeting

Features

Benefits

Cloth reinforcement

- Good strength and elongation for easy tear, application and removal
- Conformable and moisture resistant

Natural rubber based adhesive

- Clean removal from most surfaces
- High tack and aggressive adhesion for a secure bond

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	40 oz/in	4.38 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.