



Double-Coated Flame Retardant Carpet Tape



Backing Carrier:	Cloth
Adhesive:	Natural Rubber Based
Release Liner:	Blue LDPE
Standard Colors:	Natural or Black (adhesive color)
Specifications:	FAA
Standard Sizes:	48mm x 23m, 72mm x 23m

Applications

- Carpet installation on interior floors and stairs of aircraft
- Hanging and sealing acrylic plastic sheeting
- Mounting, bonding, and securing for general machine shop applications

Features

Cloth reinforcement

Flame retardant rubber-based adhesive

Benefits

- Good strength and elongation for easy tear, application and removal
- Conformable and moisture resistant
- Conformable and moisture resistant
- Clean removal from most surfaces
- Aggressive bond for secure hold
- Repositionable adhesive for easy installation

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	15 mils	0.381 mm	ASTM D-1000
Adhesion to Steel	60 oz/in	6.56 N/cm	PSTC-101
Tensile Strength	55 lb/in	96.32 N/cm	ASTM D-1000
Weight	13 oz/yd ²	440 g/m ²	ASTM D-1000
Burn Length	4.5 in		FAR 25.853(a)
Drip Exiting	N/A		FAR 25.853(a)
Exiting Time	1.5 sec		FAR 25.853(a)
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.