



PVC Color Coding & Aisle Marking Tape



Backing Carrier:	PVC Film
Adhesive:	Rubber (R306)
Release Liner:	N/A
Standard Colors:	Black, Brown, Purple, Red, Orange, White, Yellow, Blue, Green
Specifications:	A-A-1689B, Type II (supercedes PPP-T-66E, Type 1, Class 2)
Standard Sizes:	Incremental sizes 1/4" - 48" x 108Ft

Applications

- Color coding and striping
- Aisle and floor marking
- Duct and joint sealing
- Identifying safety equipment and hazards
- Harness wrapping
- Decorative packaging

Features

PVC Film Backing

Rubber Based Adhesive

Benefits

- Conformable to irregular surfaces
- Excellent solvent, chemical, moisture, and abrasion resistance
- Excellent for spiral wrapping
- Smooth, controlled unwind
- Strong bond to smooth and irregular surfaces

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	18 oz/in	1.97 N/cm	ASTM D-3330
Tensile Strength	18 lb/in	31.52 N/cm	ASTM D-3759
Elongation	250 %		
Application Temperature	-14 to 140 °F	-10 to 60 °C	
Operating Temperature	-20 to 176 °F	-29 to 80 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.