



Automotive Fineline Masking Tape



Backing Carrier: PVC Film
Adhesive: Rubber (R405)
Release Liner: N/A
Standard Colors: Blue Gloss
Standard Sizes: Incremental sizes 0.118" - 47.5" x 108Ft

Applications

- Automotive OEM fine-line and bulk masking (RIM and TPO plastics)
- Clean room paint masking
- Short-term outdoor masking
- High temperature bake cycles (280 °F up to 45m)*
- OEM paintline and powerwash operations.
- Autobody aftermarket fine-line color separations.

Features

Benefits

PVC Film Backing

Rubber Based Adhesive

Clean-cut Plastic Core

- Solvent and moisture resistant
- Handles compound and tight radius curves
- Crisp, fine-line edge
- Printable backing
- Good high temperature performance
- Clean removability after bake cycle
- Recyclable and clean - no dust or contaminants

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	26 oz/in	2.84 N/cm	ASTM D-3330
Tensile Strength	11 lb/in	19.26 N/cm	ASTM D-3759
Elongation	160 %		
Application Temperature	60 to 120 °F	16 to 49 °C	
Operating Temperature	40 to 280 °F	4.4 to 138 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.