



PVC Finline Masking Tape



- Backing Carrier:** PVC Film
- Adhesive:** Rubber (R408)
- Release Liner:** N/A
- Standard Colors:** Yellow (Matte)
- Standard Sizes:** Incremental sizes 0.118" - 55.5" x 108Ft

Applications

- Automotive OEM fine line and bulk masking (RIM and TPO plastics)
- OEM paint line and power wash cycles
- High temperature bake cycles (310 °F for 45 min)*
- Clean room paint masking

Features

Benefits

PVC Film Backing

- Tough and conformable
- Moisture and solvent resistant
- Crisp, fine line edge
- Printable and die-cuttable

Rubber Based Adhesive

- Excellent high temperature performance
- Stain and ghosting resistant

Clean-cut Plastic Core

- Recyclable and clean - no dust or contaminants

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	22 oz/in	2.41 N/cm	ASTM D-3330
Tensile Strength	17 lb/in	29.77 N/cm	ASTM D-3759
Elongation	190 %		
Application Temperature	60 to 120 °F	16 to 49 °C	
Operating Temperature	40 to 310 °F	4.4 to 154 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.