



Automotive Fineline Masking Tape



Backing Carrier: PVC Film
Adhesive: Rubber (R406)
Release Liner: N/A
Standard Colors: Lt Blue, Medium Blue (Matte)
Standard Sizes: Incremental sizes 0.118" - 47.5" x 108Ft

Applications

- Masking color separations on finished metals and plastics (TPO & RIM) fascia and trim
- Clean room paint masking
- Short-term outdoor masking
- High temperature bake cycles (280 °F up to 45 min)*
- OEM paint line and power wash operations
- Autobody aftermarket fine-line color separations.

Features

Benefits

PVC Film Backing

- Solvent and moisture resistant
- Handles compound and tight radius curves
- Crisp, fine line edge
- Non-glare matte finish

Rubber Based Adhesive

- Good high temperature performance
- Staining and ghosting resistant

Clean-cut Plastic Core

- Recyclable and clean - no dust or contaminants

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	15 oz/in	1.64 N/cm	ASTM D-3330
Tensile Strength	15 lb/in	26.27 N/cm	ASTM D-3759
Elongation	100%		
Application Temperature	60 to 120 °F	16 to 49 °C	
Operating Temperature	40 to 280 °F	4.4 to 138 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.