



9 mil Multi-Purpose Duct Tape



- Backing Carrier:** PE Coated Cloth
- Adhesive:** Rubber
- Release Liner:** N/A
- Standard Colors:** Silver, Black, Red, White, OD, Blue, Green, Brown, Tan, Yellow, Burgundy
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 48mm x 55m, 72mm x 55m

Applications

- General purpose packaging and repair
- Color coding
- Temporary holding
- Seaming and sealing PE sheeting

Features	Benefits
PE-Coated Cloth Backing	• Good balance of tensile strength and tearability • Conformable and moisture resistant • Good adhesion to a variety of surfaces • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®
Natural Rubber Based Adhesive	
Low VOC Content	

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9 mils	0.229 mm	ASTM D-1000
Adhesion to Steel	70 oz/in	7.7 N/cm	PSTC-101
Adhesion to Backing	30 oz/in	3.28 N/cm	PSTC-101
Tensile Strength	25 lb/in	43.8 N/cm	ASTM D-1000
Elongation	24 %		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.