



Acrylic Transfer Adhesive Tape



Adhesive: Acrylic (I605)
Release Liner: 80lb super-calendered, silicone release treated on both sides

Applications

- Laminating paper, felt, sponge rubber, foam, and plastic
- Mounting decorative trim and sound and vibration damping materials
- Gasket assembly
- Weather stripping

Features

Acrylic Adhesive

80lb Release Liner

Benefits

- High heat and humidity resistance
- Excellent performance over a wide temperature range
- Adheres well to foams and plastics including PE, TPO, ABS, and PP
- Non-fogging for automotive applications
- Easy to die-cut and convert

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness (with Liner)	7.3 mils	0.185 mm	PSTC 133
Adhesive Thickness	2.8 mils	0.071 mm	PSTC 133
Liner Thickness	4.5 mils	0.114 mm	PSTC 133
Adhesion to Steel	60 oz/in	6.56 N/cm	PSTC 101 Mod
Static Shear (1" x 1" x 1 kg)	168 Hours		
Laminating Temperature	50 to 150 °F	10 to 65 °C	
Continuous Use Temperature	200 °F	93 °C	
Intermittent Use Temperature	250 °F	121 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.