



11 mil Contractor Grade Duct Tape



- Backing Carrier:** PE Coated Cloth
- Adhesive:** Rubber
- Release Liner:** N/A
- Standard Colors:** Silver, Black
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 48mm x 55m, 72mm x 55m

Applications

- Hanging and seaming poly sheeting
- General purpose duct and insulation sealing
- Temporary holding and bundling
- Sealing and closure tape for poly bags
- General purpose packaging and repair

Features	Benefits
PE-Coated Cloth Backing	• Good balance of tensile strength and tearability • Conformable and moisture resistant
Natural Rubber Based Adhesive	• Aggressive high adhesion • Superior vertical hold
Low VOC Content	• Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	100 oz/in	70.61 N/cm	PSTC-101
Adhesion to Backing	45 oz/in	31.77 N/cm	PSTC-101
Tensile Strength	24 lb/in	271.16 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.