



9 mil Multi-Purpose Duct Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Silver, Black, White, Blue, Brown, Burgundy, Green, OD, Red, Tan, Yellow
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- General repair
- Bundling & securing carpets, padding and protective sheeting for the convention and hotel industry
- Bundling, patching, and mending
- Sealing off polyethylene waste disposal bags
- General purpose abatement and contractor uses
- Plumbing applications

Features

PE-Coated Cloth Backing

Natural rubber based adhesive

Low VOC Content

Benefits

- Good balance of strength & conformability
- Resists twisting & curling
- Available in 11 colors
- Moisture resistant
- Aggressive adhesion to smooth and rough surfaces
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9 mils	0.229 mm	ASTM D-1000
Adhesion to Steel	85 oz/in	9.3 N/cm	PSTC-101
Tensile Strength	24 lb/in	42.03 N/cm	ASTM D-1000
Elongation	20 %		ASTM D-1000
Flame Spread Index	5		UL 723
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.