



12 mil Premium Grade Duct Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Silver, Black
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- Hanging and seaming poly sheeting
- Water-resistant packaging and seals
- Temporary holding and bundling
- Sealing and closure tape for poly bags
- General purpose packaging and repair
- Media blast protection

Features

Benefits

PE-Coated Cloth Backing

- Good balance of tensile strength and tearability
- Conformable and moisture resistant

Natural Rubber Based Adhesive

- Aggressive high adhesion
- Superior vertical hold

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	12 mils	0.305 mm	ASTM D-1000
Adhesion to Steel	90 oz/in	63.55 N/cm	PSTC-101
Adhesion to Backing	45 oz/in	31.77 N/cm	PSTC-101
Tensile Strength	27 lb/in	305.06 N/cm	ASTM D-1000
Elongation	24 %		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.