



Single Coated Nonwoven Tape



Backing Carrier: 2.4 oz/sy white spunlace polyester nonwoven

Adhesive: Non-sensitizing medical-grade acrylic (M109)

Release Liner: 96lb white polycoated kraft, silicone treated on one side

Applications

- Electrodes: ECG, EKG, TENS
- Medical device attachment
- Wound coverings
- Island dressings

Features

Benefits

PET non-woven carrier

- Breathable for maximum patient comfort
- Highly conformable

Medical-grade Acrylic Adhesive

- Excellent adhesion to skin and drape materials
- Stable to EtO and gamma sterilization

96lb Release Liner

- Easy to die-cut and convert
- Good dimensional stability and lay flat

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness (with Liner)	22.6 mils	0.574 mm	PSTC 133
Carrier Thickness	14 mils	0.356 mm	PSTC 133
Adhesive Thickness	1.8 mils	0.046 mm	PSTC 133
Liner Thickness	6.8 mils	0.173 mm	PSTC 133
Adhesion to Steel	130 oz/in	14.22 N/cm	PSTC 101 Mod
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		