



12 mil Professional Grade Duct Tape



- Backing Carrier: PE Coated Cloth
- Adhesive: Rubber
- Release Liner: N/A
- Standard Colors: Printed Silver, Printed Black
- Specifications: Tested in accordance with UL 723
- Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Heavy duty duct and insulation sealing
- General purpose packaging and repair
- Covering thermal insulation materials
- Temporary holding and bundling

Features	Benefits
PE-Coated Cloth Backing	- Excellent tensile strength - Clean, crisp tear - Conformable and moisture resistant
Natural Rubber Based Adhesive	Superior adhesion
Low VOC Content	Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	12 mils	0.305 mm	ASTM D-1000
Adhesion to Steel	36 oz/in	3.94 N/cm	PSTC-101
Tensile Strength	28 lb/in	49.04 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.