




## 11 mil Professional Grade Metallized Duct Tape



|                         |                                  |
|-------------------------|----------------------------------|
| <b>Backing Carrier:</b> | Metallized PE Coated Cloth       |
| <b>Adhesive:</b>        | Rubber                           |
| <b>Release Liner:</b>   | N/A                              |
| <b>Standard Colors:</b> | Metallic                         |
| <b>Specifications:</b>  | Tested in accordance with UL 723 |
| <b>Standard Sizes:</b>  | 48mm x 55m, 72mm x 55m           |

### Applications

- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing environments
- General repair
- Bundling, patching, and mending

### Features

**Metallized PE-Coated Cloth Backing**

**Natural Rubber Based Adhesive**

**Low VOC Content**

### Benefits

- Excellent balance of tensile strength and tearability
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Typical Test Values

|                                        | Standard UOM | Metric UOM | Test Method |
|----------------------------------------|--------------|------------|-------------|
| <b>Total Thickness</b>                 | 11 mils      | 0.279 mm   | ASTM D-1000 |
| <b>Adhesion to Steel</b>               | 70 oz/in     | 7.66 N/cm  | PSTC-101    |
| <b>Adhesion to Backing</b>             | 48 oz/in     | 5.25 N/cm  | PSTC-101    |
| <b>Tensile Strength</b>                | 23 lb/in     | 40.28 N/cm | ASTM D-1000 |
| <b>Elongation</b>                      | 24%          |            | ASTM D-1000 |
| <b>Flame Spread Index</b>              | 10           |            |             |
| <b>Smoke Developed Index</b>           | 5            |            |             |
| <b>Operating Temperature</b>           | 40 to 200 °F | 4 to 93 °C |             |
| <b>Recommended Storage Temperature</b> | 60 to 80 °F  |            |             |
| <b>Recommended Storage Humidity</b>    | 40 to 60 %   |            |             |
| <b>Shelf Life (Standard)</b>           | 36 Months    |            |             |

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.