



11 mil Professional Grade Metalized Duct Tape



- Backing Carrier: Metallized PE Coated Cloth
- Adhesive: Rubber
- Release Liner: N/A
- Standard Colors: Metallic (Printed)
- Specifications: Tested in accordance with UL 723
- Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Duct sealing and HVAC contractor uses
 - General repair
- Maintenance applications in manufacturing environments
 - Bundling, patching, and mending

Features

- Metalized PE-Coated Cloth Backing
- Natural Rubber Based Adhesive
- Low VOC Content

Benefits

- Excellent balance of tensile strength and tearability
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	70 oz/in	7.66 N/cm	PSTC-101
Adhesion to Backing	48 oz/in	5.25 N/cm	PSTC-101
Tensile Strength	23 lb/in	40.28 N/cm	ASTM D-1000
Elongation	24%		ASTM D-1000
Flame Spread Index	10		
Smoke Developed Index	5		
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.