



13 mil Premium Grade Duct Tape



- Backing Carrier:** PE Coated Cloth
- Adhesive:** Rubber
- Release Liner:** N/A
- Standard Colors:** Silver, Black
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 48mm x 55m, 72mm x 55m

Applications

- Waterproof repairs
- Seaming and securing underlayment
- Heavy-duty contractor and manufacturing uses
- Heavy-duty packaging and bundling
- Plastering applications
- Mediablast protection

FeaturesBenefits

- | | |
|-------------------------------|---|
| PE-Coated Cloth Backing | <ul style="list-style-type: none">• High tensile strength for difficult applications• Puncture & abrasion resistance• Crisp, straight tear• Moisture, solvent & abrasion resistant |
| Natural Rubber Based Adhesive | <ul style="list-style-type: none">• Aggressive adhesion to all surfaces including concrete and other rough textures |
| Low VOC Content | <ul style="list-style-type: none">• Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED® |

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	13 mils	0.33 mm	ASTM D-1000
Adhesion to Steel	95 oz/in	10.39 N/cm	PSTC-101
Tensile Strength	50 lb/in	87.56 N/cm	ASTM D-1000
Elongation	13%		ASTM D-1000
Flame Spread Index	15		UL 723
Smoke Developed Index	20		UL 723
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.