



Professional Grade Mastic Tape

Backing Carrier: Printed Foil
Adhesive: Butyl Rubber Adhesive
Release Liner: Blue LDPE Film
Standard Colors: Aluminum
Specifications: UL 181B-FX Listed
Standard Sizes: 48mm x 10yd

Applications

- Indoor/Outdoor sealing of low, medium, and high pressure sheet metal duct systems and UL Listed flexible, non-metallic ducts
- Seal cracks and seams in gutters, sheet metal roofing, trailers, and more

Features

Aggressive butyl mastic adhesive

Conformable foil backing

UL 181B-FX Listed

Low VOC Content

Benefits

- Provides permanent water and air-tight seal
- Resistant to moisture and solvents
- Repositionable for several minutes for easy install
- Easy to use in tight spaces
- Conforms easily to round, square or odd-shaped objects
- Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	17 mils	0.432 mm	ASTM D-1000
Adhesion to Steel	90 oz/in	9.85 N/cm	PSTC-101
Adhesion to Backing	40 oz/in	4.38 N/cm	PSTC-101
Tensile Strength	23 lb/in	40.28 N/cm	ASTM D-1000
Operating Temperature	-20 to 200 °F	-28 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.