



PE Coated Fiberglass Cargo Pit Sealing Tape



Backing Carrier: Coated Fiberglass Cloth
Adhesive: Rubber
Release Liner: N/A
Standard Colors: White Printed
Specifications: FAA
Note: Colors: White Printed
Standard Sizes: 2" x 36yd, 72mm x 33M, 4" x 36yd

Applications

- Cargo pit applications for freight-carrying aircraft
- Seaming and repairing cargo compartment liners
- Media blast protection
- Challenging applications where high adhesion and flame resistance is critical
- Covering pins and rivets

Features

Coated Fiberglass Cloth

Rubber Based Adhesive

Benefits

- Super high tensile strength
- Resists flame penetration for added safety
- High moisture resistance
- Coating protects skin from contacting fiberglass
- Aggressive adhesion to all surfaces
- Maintains seal under heavy loads
- Resists flagging and lifting
- Deca-BDE Free

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	13 mils	0.33 mm	ASTM D-1000
Adhesion to Steel	38 oz/in	4.16 N/cm	PSTC-101
Tensile Strength	150 lb/in	262.69 N/cm	ASTM D-1000
Burn Length	0.25 in		FAR 25.853(a)
Flame Penetration	N/A		FAR 25.855(d)
Drip Exiting	N/A		
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.