



7 mil Utility Grade Duct Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Silver, Black
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- Maintenance and general repair
- Bundling, patching, and mending
- Joint sealing and pipe wrapping
- Heavy-duty box sealing

Features

Benefits

PE-Coated Cloth Backing

- Conformable and hand tearable
- Resists twisting and curling

Natural Rubber Adhesive

- Bonds well to most surfaces, good all climate performance

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	65 oz/in	7.11 N/cm	PSTC-101
Adhesion to Backing	38 oz/in	4.16 N/cm	PSTC-101
Tensile Strength	21 lb/in	36.78 N/cm	ASTM D-1000
Elongation	19 %		ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.