




8 mil Utility Grade Duct Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Silver, Black
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- Maintenance and general repair
- Bundling, patching, and mending
- Joint sealing and pipe wrapping
- Heavy-duty box sealing

Features

PE-Coated Cloth Backing

Natural Rubber Adhesive

Low VOC Content

Benefits

- Conformable and hand tearable
- Resists twisting and curling
- Bonds well to most surfaces
- Good all-climate performance
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	8 mils	0.203 mm	ASTM D-1000
Adhesion to Steel	70 oz/in	49.43 N/cm	PSTC-101
Tensile Strength	22 lb/in	248.57 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		