



Polypropylene Fineline Masking Tape



- Backing Carrier:** Embossed Polypropylene
- Adhesive:** Pigmented Polyurethane (U515)
- Release Liner:** N/A
- Standard Colors:** Green
- Standard Sizes:** Incremental sizes 1/8" - 48" x 180Ft

Applications

- Automotive OEM and aftermarket fine-line masking
- Masking color separations on plastic, aluminum, steel, and fiberglass

Features

Benefits

Embossed Polypropylene Backing

- Conformable
- Solvent resistant
- Transparent for easy application

Polyurethane Adhesive

- Good all temperature performance
- Holds up to many paint systems
- Excellent surface wettability

Clean-cut Plastic Core

- Splinter & fiber free for less surface contamination

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	30 oz/in	3.28 N/cm	ASTM D-3330
Tensile Strength	13 lb/in	22.77 N/cm	ASTM D-3759
Elongation	700%		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 250 °F	-40 to 121 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		