




Single Coated Foam Tape



- Backing Carrier:** 1/32" white, crosslinked polyethylene foam
- Adhesive:** Highly moisture-resistant, non-sensitizing medical grade acrylic (M110)
- Release Liner:** 96lb bleached polycoated kraft, silicone treated on one side

Applications

- Electrodes: ECG, EKG, TENS
- Medical device mounting
- AED defibrillator pads
- Transdermal delivery system

Features

Benefits

Polyethylene Foam Backing

- Soft and flexible for maximum patient comfort
- Conformable and easily adapts to medical devices and body contours

Acrylic Adhesive

- Aggressive adhesive designed for extended wear applications
- Removes cleanly without causing trauma
- Stable to EtO and gamma sterilization
- Highly resistant to perspiration-borne moisture

96lb Kraft Liner

- Easily die-cut into various shapes and sizes
- Dimensionally stable and moisture resistant

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness (with Liner)	41 mils	1.041 mm	PSTC 133
Carrier Thickness	31.2 mils	0.792 mm	PSTC 133
Adhesive Thickness	3 mils	0.076 mm	PSTC 133
Liner Thickness	6.8 mils	0.173 mm	PSTC 133
Adhesion to Steel	80 oz/in	8.75 N/cm	PSTC 101 Mod
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		