




Double-Coated Medical Film Tape



Backing Carrier: 1.0 mil polyurethane film

Adhesive AS/LS: Non-irritating medical-grade acrylic (M119)

Release Liner: 80lb bleached, silicone release treated on both sides

Applications

- Toupee attachment
- Medical device assembly
- Medical device attachment
- Surgical drape fabrication and assembly
- Surgical drape attachment: drape to drape, drape to skin

Features

Benefits

Polyurethane Film Carrier

- High breathability and conformability for extended wear and maximum patient comfort

Non-Irritating Acrylic Adhesive

- Excellent adhesion to skin and other surfaces
- Suitable for long-term wear

80lb Release Liner

- Easy to use and convert

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness (with Liner)	9.4 mils	0.239 mm	PSTC 133
Carrier Thickness	1 mils	0.025 mm	PSTC 133
Adhesive Thickness (Air Side)	2.1 mils	0.053 mm	PSTC 133
Adhesive Thickness (Liner Side)	2.1 mils	0.053 mm	PSTC 133
Liner Thickness	4.2 mils	0.107 mm	PSTC 133
Adhesion to Steel (Air Side)	100 oz/in	10.94 N/cm	PSTC-101
Adhesion to Steel (Liner Side)	110 oz/in	12.03 N/cm	PSTC 101 Mod
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.