



12 mil Premium Duct Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Silver, Black, Olive Drab
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- Heavy-duty repair and maintenance
- Waterproof packaging
- Duct and vent sealing applications
- Media-blast protection

Features

Benefits

PE-Coated Cloth Backing

- Smooth, consistent unwind
- Moisture, chemical, and abrasion resistance

Natural Rubber Adhesive

- High adhesion and excellent holding power
- Long-term moisture resistant bonds

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	12 mils	0.305 mm	ASTM D-1000
Adhesion to Steel	100 oz/in	70.61 N/cm	PSTC-101
Tensile Strength	24 lb/in	271.16 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		