



- Backing Carrier:** ASJ Kraft/Scrim/Foil Laminate
- Adhesive:** Acrylic
- Release Liner:** Polycoated Natural Kraft Paper
- Standard Colors:** White
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 72mm x 46M

Applications

- Vapor barrier seal for ASJ-faced duct board, pipe insulation, and thermal jacketing
- Sealing insulation and repairing in cooler/refrigeration applications

Features

Benefits

White Kraft/Scrim/Foil Laminate Backing

- High strength and tear resistant
- Mold resistant

Acrylic Adhesive

- Low odor adhesive
- Super high tack, aggressive bond to surfaces

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101
Tensile Strength	45 lb/in	78.81 N/cm	ASTM D-1000
WVTR	0.02 perms		ASTM E96
Flame Spread Index	5		
Smoke Developed Index	25		
Emmissivity	0.03		ASTM E408
Operating Temperature	-35 to 260 °F	-37 to 126 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.