



16 mil Super Premium Duct Tape



Backing Carrier: PE Coated Cloth

Adhesive: Rubber

Release Liner: N/A

Standard Colors: Black

Standard Sizes: 48mm x 36M

Applications

- Sealing and patching bottom board materials for manufactured housing
- Media-blast protection
- Heavy-duty contractor and manufacturing uses
- Seaming and sealing for heavy PE sheeting and tarps

Features

PE-Coated Cloth Backing

Natural Rubber Adhesive

Low VOC Content

Benefits

- High tensile strength for difficult applications
- Puncture and abrasion resistant
- Crisp, straight tear
- Moisture, solvent, and abrasion resistant
- Aggressive adhesion to all surfaces
- Excellent long term bond
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	16 mils	0.406 mm	ASTM D-1000
Adhesion to Steel	110 oz/in	12.03 N/cm	PSTC-101
Tensile Strength	48 lb/in	84.06 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		