



**Premium 13 mil Duct Tape**



|                         |                                          |
|-------------------------|------------------------------------------|
| <b>Backing Carrier:</b> | PE Coated Cloth                          |
| <b>Adhesive:</b>        | Rubber                                   |
| <b>Release Liner:</b>   | N/A                                      |
| <b>Standard Colors:</b> | Silver, Black, Red, White, OD, Dark Blue |
| <b>Specifications:</b>  | Tested in accordance with UL 723         |
| <b>Standard Sizes:</b>  | 48mm x 55m, 72mm x 55m                   |

**Applications**

- Waterproof repairs
- Seaming and securing underlayment materials
- Heavy-duty contractor and manufacturing uses
- Heavy-duty packaging and bundling
- Plastering applications
- Media-blast protection

**Features**

**Benefits**

**PE-Coated Cloth Backing**

- High tensile strength for difficult applications
- Abrasion and puncture resistant
- Crisp, straight tear
- Moisture, solvent, and chemical resistant

**Natural Rubber Adhesive**

- Aggressive adhesion to all surfaces - including extremely rough materials

**Low VOC Content**

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

**Typical Test Values**

|                                        | Standard UOM | Metric UOM | Test Method              |
|----------------------------------------|--------------|------------|--------------------------|
| <b>Total Thickness</b>                 | 13 mils      | 0.33 mm    | ASTM D-1000              |
| <b>Adhesion to Steel</b>               | 95 oz/in     | 10.39 N/cm | PSTC-101                 |
| <b>Tensile Strength</b>                | 50 lb/in     | 87.56 N/cm | ASTM D-1000              |
| <b>Elongation</b>                      | 13 %         |            | ASTM D-1000              |
| <b>Flame Spread Index</b>              | 15           |            | In accordance with UL723 |
| <b>Smoke Developed Index</b>           | 20           |            | In accordance with UL723 |
| <b>Operating Temperature</b>           | 40 to 200 °F | 4 to 93 °C |                          |
| <b>Recommended Storage Temperature</b> | 60 to 80 °F  |            |                          |
| <b>Recommended Storage Humidity</b>    | 40 to 60 %   |            |                          |
| <b>Shelf Life (Standard)</b>           | 36 Months    |            |                          |

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.