




Single Coated Foam Tape



- Backing Carrier:** 1/16" white, crosslinked polyethylene foam
- Adhesive:** Non-Sensitizing Acrylic (M108)
- Release Liner:** 74lb bleached polycoated kraft, silicone treated on one side

Applications

- Electrodes: ECG, EKG, TENS
- AED defibrillator pads
- Medical device mounting
- Transdermal delivery system

Features

Benefits

Polyethylene Foam Backing

- Soft and flexible for maximum patient comfort
- Conformable and easily adapts to medical devices and body contours

Acrylic Adhesive

- High tack bonds well to various materials
- Stable to EtO and gamma sterilization

74lb Kraft Liner

- Easily die-cut into various shapes and sizes

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness (with Liner)	70.1 mils	1.78054 mm	PSTC 133
Carrier Thickness	62.5 mils	1.5875 mm	PSTC 133
Adhesive Thickness	2 mils	0.0508 mm	PSTC 133
Liner Thickness	5.6 mils	0.14224 mm	PSTC 133
Adhesion to Steel	90 oz/in	9.846 N/cm	PSTC 101 Mod
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		