



Premium Web Spray Adhesive



Standard Colors: Light Amber

Spray Pattern: Lace/Web

Standard Sizes: 14 oz Net Wt

Applications

- Bonding carpets
- Securing labels
- Bonding fabric, insulation, plastic films, felt, rubber leather, cork, paper, cardboard, metal, wood
- Securing insulation/liner materials to duct work
- Suitable for permanent or temporary bonds
- Excellent for laminating foam materials to a variety of substrates

Features

Benefits

Rubber Based

- Fast skin, fast grab, low soak-in
- Performs over a wide temperature range
- Good UV, moisture, and oxidation resistance

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Wide Finger Pad Nozzle

- Provides increased comfort over extended use

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Solids	24% Premium Resins		
Evaporation Rate	20 to 20-30 seconds sec		
Bonding Time	1 minute to one hour to 60 min		
Operating Temperature	-10 to 180 °F	-23 to 82 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.