



ASJ-WMP Seaming Tape



- Backing Carrier:** White OPP/Scrim/Foil Laminate
- Adhesive:** Acrylic
- Release Liner:** Polycoated Natural Kraft Paper
- Standard Colors:** White
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 72mm x 46M

Applications

- Vapor barrier seal for WMP-faced industrial insulation and thermal jacketing
- Sealing insulation and repairing in cooler/refrigeration applications

Features

White Metallized OPP Film/Scrim/Kraft Facer

Acrylic Adhesive

Low VOC Content

Benefits

- High strength and tear resistant
- Excellent air barrier properties
- Mold resistant
- Low odor adhesive
- Super high tack, aggressive bond to surfaces
- Excellent low or high temperature performance
- Can contribute toward satisfying EQ Credit 4.1 mold resistant

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	8.8 mils	0.224 mm	ASTM D-1000
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101
Tensile Strength	45 lb/in	78.81 N/cm	ASTM D-1000
Operating Temperature	-35 to 260 °F	-37 to 126 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.