



Polypropylene Water Filter Outerwrap Tape



- Backing Carrier:** Unidirectional Polypropylene
- Adhesive:** Permanent Acrylic (A100)
- Release Liner:** N/A
- Standard Colors:** Blue, White
- Specifications:** Registered with NSF through Supporting Material information (AESOP 6928).
- Standard Sizes:** Incremental sizes 1.5" - 52" x LY

Applications

- Seamless outer wrap for reverse osmosis water filters - replaces spiral wrapped PVC tape

Features	Benefits
Unidirectional Polypropylene	• Excellent dimensional stability & high strength • Smooth, easy unwind • Moisture and abrasion resistant • Bright, glossy, opaque finish
Acrylic Adhesive	• Permanent adhesion for long term protection • Excellent temperature resistance

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	45 oz/in	4.92 N/cm	ASTM D-3330
Tensile Strength	150 lb/in	262.69 N/cm	ASTM D-3759
Elongation	37 %		
Application Temperature	65 to 120 °F	18 to 49 °C	
Operating Temperature	-40 to 250 °F	-40 to 121 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		