




11 mil Metallized Duct Tape



Backing Carrier: Metallized PE Coated Cloth

Adhesive: Rubber

Release Liner: N/A

Standard Colors: Metallic

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Duct sealing for flexible and rigid duct where UL Listing is not required
- Patch, bundle, repair, and mending applications throughout the HVAC jobsite
- Sealing and patching insulation materials

Features

Metallized PE-Coated Cloth Backing

Reformulated Rubber Adhesive

Low VOC Content

Benefits

- Conformable and aesthetically similar to most HVAC duct and insulation systems
- Improved strength and durability for severe use with no delamination
- Clean, straight tear for speedy installs and professional appearance
- Aggressive adhesion to metal, fiberglass, and flex duct systems
- Permanent bond to reflective/bubble insulation
- Improved cold weather performance
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	85 oz/in	9.3 N/cm	PSTC-101
Tensile Strength	50 lb/in	87.56 N/cm	ASTM D-1000
Elongation	22%		ASTM D-1000
Operating Temperature	30 to 200 °F	-1 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.