



Polypropylene Graphics Protection Tape



- Backing Carrier:** Embossed Polypropylene
- Adhesive:** Silicone (S605)
- Release Liner:** N/A
- Standard Colors:** Transparent
- Standard Sizes:** Incremental sizes 1/4in - 58in x 108Ft

Applications

- Graphics protection for skis, snowboards, and outdoor equipment
- Protective mask for surfaces during lamination, molding, or machining where clean removal is critical
- Sublimation print (170 °C press temp)

Features

Embossed polypropylene backing

Silicone Adhesive

Benefits

- Conformable and heat resistant
- Transparent for easy inspection of surfaces
- Abrasion and moisture resistant
- Does not lift during molding or shaping
- Smooth, easy unwind
- Removes cleanly from most surfaces - no residue upon removal
- Excellent extreme temperature performance

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	30 oz/in	3.28 N/cm	ASTM D-3330
Tensile Strength	14 lb/in	24.52 N/cm	ASTM D-3759
Elongation	700 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 350 °F	-40 to 176 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.