



11 mil Professional Grade Duct Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	White, Yellow, Silver Silver, Black, White, Blue, Brown, Green OD, Red, Yellow Black
Specifications:	Meets NRC Reg 1.38 & ASME NQA-1 Tested in accordance with UL 723 Tested in accordance with UL 723 Delphi Packard (GM) M0537, FMVSS-302, RoHS Compliant FMVSS-302, RoHS Compliant
Standard Sizes:	48mm x 55m, 72mm x 55m 1.5in x 60yd, 48mm x 55m 1.5" x 60yd, 48mm x 55m

Applications

- Hanging and patching polyethylene sheeting
- Maintenance applications in manufacturing environments
- Sealing polyethylene waste disposal bags
- Duct sealing and HVAC contractor uses
- Seaming and securing underlayment materials
- Color coding

Features

Benefits

PE-Coated Cloth Backing

Natural Rubber Adhesive

Low VOC Content

- Excellent balance of tensile strength and tearability
- Available in a wide range of colors
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	0.279 mm	ASTM D-1000
Adhesion to Steel	99 oz/in	10.8 N/cm	PSTC-101
Tensile Strength	23 lb/in	40.3 N/cm	ASTM D-1000
Elongation	21 %		ASTM D-1000
Flame Spread Index	5		UL 723
Smoke Developed Index	5		UL 723
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.