



Low VOC Multi-Purpose Spray Adhesive

Standard Colors: Light Amber

Spray Pattern: Lace/Web

Applications

- Bonding carpets
- Securing labels
- Bonding fabric, insulation, plastic films, felt, rubber leather, cork, paper, cardboard, metal, wood
- Securing insulation/liner materials to duct work
- Suitable for permanent or temporary bonds
- Excellent for laminating urethane foam to a variety of substrates

Features

Benefits

Rubber Based

- Fast skin, fast grab, low soak-in
- Good UV, moisture, and oxidation resistance

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Wide Finger Pad Nozzle

- Provides increased comfort over extended use

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Solids	0.22		
Evaporation Rate	30-45 seconds sec		
Application Temperature	40 to 110 °F	4 to 43 °C	
Bonding Time	1 minute to one hour min		
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.