



Extreme Weather FSK Tape



Backing Carrier:	Foil/Scrim/Kraft Paper Laminate
Adhesive:	Acrylic
Release Liner:	Unbleached Natural Kraft Paper
Standard Colors:	Aluminum
Specifications:	UL 723 Classified (72mm)
Standard Sizes:	72mm x 46M

Applications

- Vapor barrier seal for insulation facing
- Sealing insulation and repairing in cooler/refrigeration applications

Features

Benefits

Foil/Scrim/Kraft Laminate Backing

High Performance Acrylic Adhesive

UL 723 Classified

Low VOC Content

- High strength and tear resistant
- UV, moisture, and mold resistant
- Low odor and low VOC content
- High tack, aggressive bond to surfaces
- Excellent performance in extreme cold or heat
- Meets flammability requirements for use in construction and marine applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9.5 mils	0.241 mm	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	ASTM D-1000
Tensile Strength	33 lb/in	57.79 N/cm	ASTM D-1000
WVTR	>0.02 perms		Mocon (100° F, 90% RH)
VOC Content	<30 g/L		
Application Temperature	-5 °F	-20 °C	
Operating Temperature	-35 to 260 °F	-37 to 127 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.