



Low-Gloss Duct Tape



- Backing Carrier: Matte-Finish PE-Coated Cloth
- Adhesive: Rubber
- Release Liner: N/A
- Standard Colors: Black
- Specifications: Tested in accordance with UL 723
- Standard Sizes: 48mm x 45yd, 72mm x 45yd

Applications

- "AV Cord Tape" - Protect and anchor wiring for photography, film, live entertainment, meetings, and conventions
- Wrapping or bundling wire, metals, and plastics
- General repair
- Bookbinding and seam reinforcement
- Color Coding

Features

Low-Gloss PE Coated Cloth

Natural Rubber Adhesive

Low VOC Content

Benefits

- Matte-finish for less reflectivity and low sheen
- Strong and abrasion resistant
- Moisture & solvent resistant
- High tack for a variety of surfaces
- Clean removal - no residue
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	10.5 mils	0.267 mm	ASTM D-1000
Adhesion to Steel	66 oz/in	7.22 N/cm	PSTC-101
Adhesion to Backing	39 oz/in	4.27 N/cm	PSTC-101
Tensile Strength	50 lb/in	87.56 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.