



Clear Polyethylene Film Tape

Backing Carrier: LDPE Film
Adhesive: Acrylic (A100)
Release Liner: 53# Coated Kraft
Standard Colors: Clear

Applications

- General purpose sealing
 - Indoor surface protection
 - Temporary hold down
- Splicing and seaming
 - Bondbreaker tape
 - Material processing

Features

LDPE Film

Acrylic Adhesive

Benefits

- Conformable for irregular surfaces
- Transparent for less visible repairs and easy inspection
- Excellent moisture barrier properties
- High adhesion and cohesion
- Excellent high and low temperature performance
- Will not crack or crease
- Permanent bond with virtually no edge bleed
- Excellent long-term stability

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	5.5 mils	0.140 mm	PSTC-133
Adhesion to Steel	50 oz/in	5.47 N/cm	ASTM D-3330
Tensile Strength	11 lb/in	19.26 N/cm	ASTM D-3759
Elongation	400%		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.