



Clear Polyethylene Tape

- Backing Carrier:** LDPE Film
- Adhesive:** Rubber (R400)
- Release Liner:** N/A
- Standard Colors:** Clear
- Note:** Colors: Clear
- Standard Sizes:** Incremental widths 1/4" - 54" x 108ft

Applications

- General purpose sealing
- Indoor surface protection
- Temporary hold down
- Splicing and seaming
- Bondbreaker Tape
- Material processing

Features

LDPE Film

Rubber Adhesive

Benefits

- Conformable for irregular surfaces
- Transparent for less visible repairs and easy inspection
- Excellent moisture barrier properties
- Stands up to mechanical and chemical wear
- Adheres well to a wide variety of surfaces
- Excellent surface wetability
- Solvent and moisture resistant

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	5.5 mils	0.1397 mm	PSTC-133
Carrier Thickness	4.5 mils	0.1143 mm	PSTC-133
Adhesion to Steel	25 oz/in	2.74 N/cm	ASTM D-3330
Tensile Strength	11 lb/in	19.26 N/cm	ASTM D-3759
Elongation	400%		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.