



Static Port Protection Tape



- Backing Carrier:** LDPE Film
- Adhesive:** Acrylic
- Release Liner:** N/A
- Standard Colors:** Gloss Yellow, Orange, Red (Other Colors Available)
- Standard Sizes:** Incremental widths 1/4" - 54" x 108ft Easy-Tear Version & Master Rolls Available

Applications

- High visibility masking of critical static ports*
- Temporary holding and sealing
- Temporary attachment and splicing of masking materials
- Color coding and part marking
- Temporary outdoor surface protection

Features

LDPE Film

Acrylic Adhesive

Benefits

- Conformable for irregular surfaces
- Withstands temporary outdoor exposure
- Excellent moisture barrier properties
- Resistant to citrus-based cleaners
- Solvent resistant - holds up to power washing
- UV Resistant (removes clean up to 28 days)
- Firm bond with virtually no edge bleed
- Will not crack or crease
- Excellent high and low temperature performance

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	5.5 mils	0.14 mm	PSTC-133
Adhesion to Steel	50 oz/in	5.47 N/cm	ASTM D-3330
Tensile Strength	11 lb/in	19.26 N/cm	ASTM D-3759
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.