



LDPE Greenhouse Patch Tape



- Backing Carrier:** LDPE Film
- Adhesive:** Acrylic (A100)
- Release Liner:** N/A
- Standard Colors:** Clear
- Standard Sizes:** Incremental widths 1/4" - 54" x 108ft

Applications

- Patching and seaming of greenhouse films
- Temporary hold down
- General purpose sealing, splicing, and patching

Features

LDPE Film

Acrylic Adhesive

Benefits

- Conforms well to irregular surfaces
- Withstands short-term exposure to the elements
- Excellent moisture barrier
- Optically clear and hand tearable
- High adhesion and cohesion
- Excellent all temperature performance
- Excellent long-term stability

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	50 oz/in	5.47 N/cm	ASTM D-3330
Tensile Strength	11 lb/in	19.26 N/cm	ASTM D-3759
Elongation	400 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.