



5075 Wire Harness Attachment Tape



Backing Carrier: Low Density Polyethylene
Adhesive: Acrylic (A276)
Release Liner: 66# Clay Coated Paper Liner
Standard Colors: Black, Clear
Specifications: GM 9986080

Applications

- Wire harness attachment to headliners, flooring, and other surfaces in automotive, marine, recreational equipment, construction, and more
- Anti-squeak, anti-itch headliner barrier
- Permanent surface attachments
- Alternative to commonly used foil tapes

Features

Low-density PE Film Backing

Acrylic Adhesive

66# Paper Liner

Benefits

- Conformable for curves and irregular surfaces
- Low weight, cost effective alternative to foil
- Aggressive and permanent bond to headliner and harness surfaces
- Strong, locking bond to fabrics
- Excellent longevity
- Excellent high and low temperature performance
- Smooth clean release - easy to use
- Die cuttable

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7 mils	0.178 mm	PSTC-133
Thickness (Backing Thickness)	4.5 mils	0.114 mm	
Adhesive Thickness	2.5 mils	0.064 mm	PSTC 133
Adhesion to Steel	120 oz/in	13.13 N/cm	ASTM D-3330
Tensile Strength	11.5 lb/in	20.14 N/cm	ASTM D-3759
Elongation	500 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.