



5097 Preservation and Sealing Tape



Backing Carrier: UV Stabilized LDPE Film

Adhesive: Acrylic (A128)

Release Liner: 53# Coated Kraft

Standard Colors: White

Applications

- Long-term preservation, sealing, and splicing
- Splicing, seaming, and sealing polyethylene films
- Direct protective mask on aircraft, trucks, boats, and industrial equipment during outdoor storage
- Used in conjunction with outdoor shrink film to secure film and seal film edges during transport or extended outdoor storage

Features

LDPE Film

Acrylic Adhesive

53# Coated Kraft Liner

Benefits

- Conformable for irregular surfaces
- Abrasion resistant
- UV and weather resistant
- Moisture, solvent, and chemical resistant
- Good quick stick
- Excellent adhesion to PE and shrink film
- Excellent low-temperature adhesion
- Easy to use at wide widths

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	90 oz/in	9.85 N/cm	ASTM D-3330
Tensile Strength	18 lb/in	31.52 N/cm	ASTM D-3759
Elongation	600 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 200 °F	-40 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.