



- Backing Carrier:** PTFE Film
- Adhesive:** N/A
- Release Liner:** N/A
- Standard Colors:** White
- Note:** Colors: White
- Standard Sizes:** 0.5" x 520", 0.75" x 520", 1" x 520" | Unlimited

Applications

- Self-lubricating tape for wrapping threads at pipe connections making them easy to assemble and disassemble.
- Extends fatigue life of sealed connections and eliminates system contamination common with messy liquid and paste sealants.

Features

PTFE Film

Benefits

- Self-lubricates
- Easy to use
- Increases ease of assembly
- Unlimited shelf life

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.5 mils	0.089 mm	ASTM D-1000
Operating Temperature	-450 to 500 °F	-267 to 260 °C	
Temperature Rating	-450 to 500 °F	-267 to 260 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	Unlimited		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.