



Premium Preservation & Sealing Tape



- Backing Carrier:** UV Stabilized LDPE Film
- Adhesive:** Urethane (U514)
- Release Liner:** N/A
- Standard Colors:** White
- Standard Sizes:** Incremental widths 1/4" - 48" x 108ft

Applications

- Long-term preservation, sealing, and splicing
- Splicing, seaming, and sealing polyethylene films
- Direct protective mask on aircraft, trucks, boats, or industrial equipment during outdoor storage
- Used in conjunction with outdoor shrink film to secure film and seal film edges during transport or extended outdoor storage

Features

LDPE Film

Urethane Adhesive

Benefits

- Excellent chemical and solvent resistance
- Highly conformable
- Stands up to extreme environmental conditions
- Moisture resistant
- Aggressive bond
- Controlled unwind
- Easy to apply even at wide widths
- Will not lift or flag
- Excellent low-temperature adhesion

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	65 oz/in	7.11 N/cm	ASTM D-3330
Tensile Strength	18 lb/in	31.52 N/cm	ASTM D-3759
Elongation	650 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 200 °F	-40 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.