



Premium Preservation & Sealing Tape

- Backing Carrier:** LDPE Film
- Adhesive:** Rubber
- Release Liner:** N/A
- Standard Colors:** White
- Standard Sizes:** Incremental widths 1/4" - 48" x 108ft

Applications

- Long-term preservation, sealing, and splicing
- Splicing, seaming, and sealing polyethylene films
- Direct protective mask on aircraft, trucks, boats, and industrial equipment during outdoor storage
- Used in conjunction with outdoor shrink film to secure film and seal film edges during transport or extended outdoor storage

Features

- LDPE Film**
- Rubber Adhesive**

Benefits

- UV and weather resistant
- Will not break down after extended outdoor exposure
- Adheres firmly to contoured and irregular surfaces
- Will not leave residue, stains, or ghosting on most surfaces

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	25 oz/in	2.74 N/cm	ASTM D-3330
Tensile Strength	17 lb/in	29.77 N/cm	ASTM D-3759
Elongation	45000 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 180 °F	-40 to 82 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.